

GT P02.09 SC

ArticleNo. 54981

FBGT054981

General information

Product group	High Performance Flat Belts
Product sub type	Classic
Industry segment(s)	Textile, Logistics
Application(s)	Spindle tape
Main product feature(s)	-
Indication(s) of use	-

Belt construction

Top side	material	Mixed fabric
	finish	Fabric texture
	color	Black
Tension member		Polyamide fabric
Bottom side / Pulley side	material	NBR elastomer
	finish	Smooth
	color	Green

Characteristics

Food Grade	NO
Antistatic (AS)	YES
High conductive (HC)	NO
ATEX	NO

Technical belt data

Belt thickness	DIN EN ISO 2286-3	0.9 mm
Belt thickness tolerance	+/-	0.1 mm
Weight	DIN EN ISO 290703-1	0.8 kg/m ²
Force at 1 % elongation static	DIN EN ISO 21181	5.0 N/mm
Force at 1 % elongation dynamic	DIN EN ISO 21181	2.0 N/mm
Recommended elongation	from/to	0.5 / 2.0 %
Coefficient of friction, bottom (pulley) side to steel, dynamic	DIN EN ISO 21182	0.6 μ
Coefficient of friction, top side to steel, dynamic	DIN EN ISO 21182	0.2 μ
Min. pulley diameter	flexing	15 mm
	back flexing	15 mm
Temperature range	from/to	+0 / +80 °C
Standard sales width		600.0 mm

Endless method

Recommended splice method	WedgeSkive75D-0.5-1.4
Alternative splice method	-

Additional information

The information applies at approx. 20°C/68°F and 65% relative humidity.

Consult our specialists for further instructions regarding joining, storage & maintenance, tracking & tensioning.

Consult our specialists for calculations with our E-RappCalc technical calculation program.

Because of continuous development, the presented data is subject to alteration. This data replaces that included in previous publications. Ammeraal Beltech excludes any liability for the incorrect use of the above stated information. Subject to the general terms and conditions of sale and delivery, as applied by its operating companies, are all activities performed and services rendered by Ammeraal Beltech.